



GRAINS FIXES SL/D

Garniture mécanique normalisée de 12 à 30 mm
de diamètre d'arbre.
Pression maxi 6 bar

Vitesse 15 m/s.
Température -30 °C à + 110 °C.
Selon DIN 24960

		Grain fixe SL/D			Ks - Ni		
Face fixe	Carbure de Silicium	TYPE	Ø d Arbre	Ø D2 Extérieur	L2 Epaisseur	CODE	P.U. HT €
Joint	Nitrile						
		SL/D 12	12	23	8,5		8.24
		SL/D 14	14	25	8,5		9.96
		SL/D 16	16	27	8,5		13.34
		SL/D 18	18	33	10		16.42
		SL/D 20	20	35	10		17.31
		SL/D 22	22	37	10		18.70
		SL/D 24	24	39	10		22.17
		SL/D 25	25	40	10		23.61
		SL/D 28	28	43	10		26.91
		SL/D 30	30	45	10		29.02
		SL/D 32	32	48	10		31.23
		SL/D 35	35	50	11		33.72
		SL/D 38	38	56	11		43.23
		SL/D 40	40	58	11		47.14

		Grain fixe SL/D			Ks - Vi		
Face fixe	Carbure de Silicium	TYPE	Ø d Arbre	Ø D2 Extérieur	L2 Epaisseur	CODE	P.U. HT €
Joint	Viton						
		SL/D 12	12	23	8,5		10.38
		SL/D 14	14	25	8,5		12.41
		SL/D 16	16	27	8,5		14.74
		SL/D 18	18	33	10		18.59
		SL/D 20	20	35	10		19.15
		SL/D 22	22	37	10		20.69
		SL/D 24	24	39	10		24.53
		SL/D 25	25	40	10		26.11
		SL/D 28	28	43	10		29.76
		SL/D 30	30	45	10		32.09
		SL/D 32	32	48	10		34.54
		SL/D 35	35	50	11		37.29
		SL/D 38	38	56	11		47.82
		SL/D 40	40	58	11		52.15



GARNITURES COMPLÈTES SB

Sens de rotation indifférent.

 Garniture mécanique
Pression maxi 3 bar.

 Vitesse 10 m/s.
Température -20 °C à + 100 °C.

		Bague mobile + Grain fixe SB						Ca - Ce - Ni - I4		
Face mobile	Carbone	TYPE	Ø d Arbre	Ø D1 Ext. mob	L1a Ep. Mob	L1b Ep. mob	Ø D2 Ext. fixe	L2 Ép. fixe	CODE	P.U. HT €
Face fixe	Céramique	SB 12 A	12	30	5,5	9,5	24	4,5	543 594	8.86
Joint	Nitrile	SB 13	13	30	5,2	8,5	25	5	543 608	9.60
Ressort + part.métal	Inox Aisi 304	SB 15	15	30	7	9	21,5	6,8	543 616	10.56
		SB 17	17	35	10,5	9	25	7,5	543 624	13.29
		SB 20	20	40	12	10,5	36	7	543 632	18.38

Ressort comprimé

GARNITURES COMPLÈTES SF

Sens de rotation indifférent.

		Bague mobile + Grain fixe SF - Ca - Ce - Ni - I4								
Face mobile	Carbone	TYPE	Ø d Arbre	Ø D1 Ext.mob.	L1a Ep. Mob	L1b Ep. Mob.	Ø D2 Ext. fixe	L2 Ép. fixe	CODE	P.U. HT €
Face fixe	Céramique	SF 1/2"	14,2	30	5	8	25,4	6,2	543 500	7.46
Joint	Nitrile	SF 5/8"	18,2	36,5	6,7	8	31,75	10,3	543 519	9.20
Ressort + part.métal	Inox Aisi 304	SF 3/4"	21,2	40	6	9,5	34,925	10,3	543 527	11.16
		SF 1"	26,4	47	7,9	10	41,275	11,1	543 535	13.83

Ressort comprimé