

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS



Safety Data Sheet dated 23/3/2023, version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: GRAPHITE BASED LUBRICANT FOR LOCKS

Trade code: VMD93

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description/Use: Lubricant protective

Uses not recommended: Any use not specified in this section or in section 7.3

1.3. Details of the supplier of the safety data sheet

Company:

V.M.D. ITALIA SRL - Via Amerigo Vespucci, 9 - 26010 Ripalta Cremasca (CR) - Italia

Telefono: +39-0373268299 Fax: +39-0373688982

Competent person responsible for the safety data sheet:

laboratorio@vmditalia.it

1.4. Emergency telephone number

Telefono: +39-0373268299 Fax: +39-0373688982

From Monday to Thursday 8,30-12,30 13,30-17,30

Friday 8,30-12,30 13,30-16,00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):



Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.



Warning, Eye Irrit. 2, Causes serious eye irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P102 Keep out of reach of children.

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

methyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards








SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.



3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 55\%$ - $< 60\%$	methyl acetate	Index number: 607-021-00-X CAS: 79-20-9 EC: 201-185-2 Nr. Reg.: 01-21194592 11-47-XXXX	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066
$\geq 20\%$ - $< 25\%$	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 Nr. Reg.: 01-21194869 44-21-XXXX	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280
$\geq 10\%$ - $< 12.5\%$	butane	Index number: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7 Nr. Reg.: 01-21194746 91-32-XXXX	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

>= 5% - < 7%	and isobutane	Index number: CAS: EC: Nr. Reg.:	601-004-00-0 75-28-5 200-857-2 01-21194853 95-27-XXXX	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280
-----------------	---------------	---	---	---

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl acetate - CAS: 79-20-9

ACGIH - TWA(8h): 200 ppm - STEL: 250 ppm - Notes: Headache, dizziness, nausea, eye dam (degeneration of ganglion cells in the retina)

propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

and isobutane - CAS: 75-28-5

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value
Appearance and colour:	Liquid black
Odour:	Characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Flash point:	< 0°C
Evaporation rate:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour pressure:	N.A.
Vapour density:	N.A.
Relative density:	0,9 gr/ml c.ca
Solubility in water:	Insoluble
Solubility in oil:	Total
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	N.A.
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Properties	Value
Miscibility:	N.A.
Fat Solubility:	N.A.

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - Stable under normal conditions
- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
 - It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), and nitrides.
 - It may catch fire on contact with oxidising mineral acids, powerful oxidising agents, and powerful reducing agents.
- 10.4. Conditions to avoid
 - Stable under normal conditions.
- 10.5. Incompatible materials
 - Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
 - None.

SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
 - Toxicological information of the product:
 - N.A.
 - Toxicological information of the main substances found in the product:
 - N.A.
 - If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:
 - a) acute toxicity;
 - b) skin corrosion/irritation;
 - c) serious eye damage/irritation;
 - d) respiratory or skin sensitisation;
 - e) germ cell mutagenicity;
 - f) carcinogenicity;
 - g) reproductive toxicity;
 - h) STOT-single exposure;
 - i) STOT-repeated exposure;
 - j) aspiration hazard.
- 11.2. Information on other hazards
 - Endocrine disrupting properties:
 - No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

- 12.1. Toxicity
 - Adopt good working practices, so that the product is not released into the environment.
 - N.A.
- 12.2. Persistence and degradability
 - None
 - N.A.
- 12.3. Bioaccumulative potential
 - N.A.

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
No endocrine disruptor substances present in concentration $\geq 0.1\%$
- 12.7. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

- 14.1 UN number:
ADR-UN number: UN 1950
IATA-UN number: UN 1950
IMDG-UN number: UN 1950
- 14.2 UN proper shipping name:
ADR-Shipping Name: Aerosol
IATA-Technical name: Aerosol
IMDG-Technical name: Aerosol
- 14.3 Transport hazard class(es):
ADR-Class: 2
ADR-Label: UN 1950 Aerosols – Limited quantity
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2
IMDG-Label: UN 1950 Aerosols – Limited quantity
- 14.4 Packing Group:
ADR-Packing Group: n.a
- 14.5 Environmental hazards
Marine pollutant: no
- 14.6 Special Precautions for User
IMDG-Technical name: Aerosols
Limited Quantity: max 1000ml Total gross mass of Package not exceed 30 kg LQ2
IMDG-EMS: F-D
IMDG-MFAG: S-U
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
N.a.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 2020/878
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P3a

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Safety Data Sheet

VMD75 GRAPHITE BASED LUBRICANT FOR LOCKS

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date.

It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.